

# RENOVATION™

*Acoustical Shielding for Retrofit Wall Applications*

## Product Attributes:

- Installs easily with an adhesive, like wallpaper.
- Acts as a sound, air and moisture barrier.
- Meets interior smoke and fire standards.

## Technical Specifications:

- Roll Weight = 101 Lbs.
- Roll Size = 4' x 30' / 120 square feet
- Product = EVA
- R Value = > .3
- Flame Spread = 5 Class A
- Smoke Developed Index = 5 Class A
- Passed ASTM E 84 Fire & Smoke Test
- Tested in accordance w/ ASTM D3273-00 (2005)



## Application Instructions:

1. Simply apply premium vinyl flooring adhesive with 3/32 inch V notched trowel.
2. Place RENOVATION Acoustical Shielding in position at top of wall.
3. Lower sheet along wall being careful not to get adhesive on the face surface of RENOVATION Acoustical Shielding.
4. Insert staples along top edge of sheet to hold in place. 3-4 staples per sheet should be sufficient to temporarily hold sheet in place until adhesive dries.
5. Using your hands apply light pressure to RENOVATION Acoustical Shielding sheet to ensure full contact with adhesive surface.
6. With a sweeping motion of your hands force all trapped air from behind the sheet towards the edges. This will ensure full contact with the wall and provide a smooth ready to paint surface.
7. For each additional sheet of RENOVATION Acoustical Shielding to be installed repeat step one; applying adhesive using V notched trowel as you install sheet.
8. Repeat sheet placement and installation as performed on prior sheet placing edges together to form a tight seam with no gaps.
9. Remove excess adhesive along the seam joint to minimize surface irregularities.
10. Apply thin line of wall spackle along the seam.
11. Dress the seam with a damp rag or sponge to remove excess spackle. This is done with a cross seam wiping motion.
12. Allow spackle to dry before painting.
13. Apply paint as you would to any drywall surface, prime; drywall texture or apply wall paper covering.



**Construction Materials International, Inc**  
Address: 202 East 7th Avenue, Tampa, Florida 33602, USA  
Tel: (+1)813-287-8265 / Fax: (+1) 813-287-8144  
Email: [sales@awg-llc.com](mailto:sales@awg-llc.com) / Web: [www.cmi-us.com](http://www.cmi-us.com)

