

TAM-PRO 803 WET OR DRY SURFACE PLASTIC ROOFING CEMENT

PRODUCT DATA

DESCRIPTION

An all-weather roofing mastic containing special modifiers to enhance bonding to damp surfaces. Contains select asphalts, petroleum solvents, tough reinforcing fibers, and wetting agents. Dries to form a durable, but pliable, seal that allows for minor expansion and contraction. **100% ASBESTOS FREE!**

USES

Flashing construction and other detail roofing work such as tie-offs or shingle securement. Provides excellent waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.

APPLICATION

Apply with a trowel or knife. One gallon covers 12.5 sq.ft. to an 1/8" thickness.

APPLICABLE STANDARDS

ASTM D 4586 Type I Standard Specification for Asphalt Roof Cement.

ASTM D 3409 Standard Test Method for Adhesion of Asphalt Roof Cement to Damp, Wet, or Under-water Surfaces.

Miami-Dade County Product Control Approved
NOA 08-0423.16 Expiration Date 07/24/13

CAUTION: This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified "extracts of steam and air-refined bitumens" (cutback asphalt) as "possibly carcinogenic to humans." The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.



PRODUCT NUMBER

30002145 – 3 GAL – Green Cove Springs FL
30001235 – 5 GAL – Green Cove Springs FL
30001236 – (WG) 5 GAL – Green Cove Springs FL
30001237 – (SEMI) 5 GAL – Green Cove Springs FL
30001621 – 3 GAL – Columbus KS
30001234 – (WG) 3 GAL – Columbus KS
30001622 – 5 GAL – Columbus KS
30001623 – (WG) 5 GAL – Columbus KS

For Technical Services call 800-641-4691.

TYPICAL PHYSICAL PROPERTIES*

	MIN	MAX	METHOD
Total solids (non-volatile), %	75	85	D 4586
Volatiles, %	15	25	D 4586
Flash Point, F	100	--	D 92
Asphalt, %	35	65	D 4
Viscosity, Cone Penetration @ 77 F, 1/10 mm	265	295	
VOC, grams/litre	--	300	

*All values stated as nominal

tamko.com



Construction Materials International, Inc.

Address: 202 East 7th Avenue, Tampa, Florida 33602, USA
Tel: (+1) 813-287-8265 / Fax: (+1) 813-287-8144
Email: sales@awg-llc.com / Web: www.cmi-us.com

TAMKO® and TAM-PRO® are registered trademarks of TAMKO Building Products, Inc.

©2012 TAMKO Building Products, Inc.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TAMKO
BUILDING PRODUCTS