

TAM-PRO® Q-5 HEAVY-BODIED FLASHING CEMENT

DESCRIPTION

A heavy-bodied all-weather trowel-grade mastic that contains select asphalts, petroleum solvents, tough reinforcing fibers, and special additives that enhance spreadability. Dries to form a durable, but pliable, seal that allows for minor expansion and contraction. Acid and alkali resistant, it bonds to all clean surfaces except coal tar-based materials. **100% ASBESTOS FREE!**

USES

Flashing construction and other detail roofing work such as tie-offs or shingle securement. Provides excellent waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.

APPLICATION

Apply with a trowel or knife. One gallon covers 12.5 sq.ft. to an 1/8" thickness.

PRODUCT NUMBER

- 30001240 – 3 GAL – Green Cove Springs FL
- 30001241 – (WG) 3 GAL – Green Cove Springs FL
- 30001242 – 5 GAL – Green Cove Springs FL
- 30001243 – (WG) 5 GAL – Green Cove Springs FL
- 30001244 – (SEMI) 5 GAL – Green Cove Springs FL
- 30001624 – 3 GAL – Columbus KS
- 30001625 – (WG) 3 GAL – Columbus KS
- 30001626 – 5 GAL – Columbus KS
- 30001627 – (WG) 5 GAL – Columbus KS



APPLICABLE STANDARDS

ASTM D 4586 Type I Standard Specification for Asphalt Roof Cement
 ASTM D 3409 Standard Test Method for Adhesion of Asphalt Roof Cement to Damp, Wet, or Underwater Surfaces. Miami-Dade County Product Control Approved NOA 08-0423.16 Expiration Date 07/24/13

TYPICAL PHYSICAL PROPERTIES*

	MIN	MAX	METHOD
Total solids (non-volatile), %	70	--	D 4586
Volatiles, %	20	30	D 4586
Flash Point, F	100	--	D 92
Asphalt, %	35	65	D 4
Viscosity, Cone Penetration @ 77 F, 1/10 mm	270	290	
VOC, grams/litre	--	300	

*All values stated as nominal

For Technical Services call 800-641-4691.

CAUTION: This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified "extracts of steam and air-refined bitumens" (cutback asphalt) as "possibly carcinogenic to humans." The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.



tamko.com



Construction Materials International, Inc.

Address: 202 East 7th Avenue, Tampa, Florida 33602, USA
 Tel: (+1) 813-287-8265 / Fax: (+1) 813-287-8144
 Email: sales@awg-llc.com / Web: www.cmi-us.com

TAMKO® and TAM-PRO® are registered trademarks of TAMKO Building Products, Inc.

©2012 TAMKO Building Products, Inc.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.