

VERSA-BASE®

Fiberglass SBS Modified Base Sheet

PRODUCT DATA

DESCRIPTION

VERSA-BASE® consists of a TAMKO® fiberglass mat coated on both sides with SBS rubber modified asphalt.

USES

Base ply in select 100, 200, 700 and 1000 Specifications and as an alternate for TAMKO Glass-Base® or Type 43 Coated Base Sheet in any TAMKO specification. Easily applied by mopping in hot asphalt, by mechanically fastening or with approved cold adhesive.

ADVANTAGES

- Minimal dead load weight
- High tensile strength
- Puncture resistant
- Combined strengths of fiberglass mat and SBS modified asphalt
- Excellent pliability and nail pull through resistance
- 5 year limited material warranty*

** See complete limited warranty at tamko.com for details

CERTIFICATIONS

U.L. Base / Ply Sheet Label
FM Approved**
ASTM D 6163, Type I
Miami Dade County Approved

**Refer to FMRC Approval Guide.

TYPICAL PHYSICAL PROPERTIES

Tensile Strength MD = 168 LBF/IN
(@0 deg F & 0.08 in/min) CD = 86 LBF/IN

Elongation MD = 4%
(@0 deg F & 0.08 in/min) CD = 3%

Tear Strength MD = 99 LBS
CD = 89 LBS

Low Temp Flex (PASS)



CAUTION: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known" human carcinogens by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

Use of this product in "hot mopped" applications may expose workers and others in the work area to oxidized asphalt and its emissions. The International Agency for Research on Cancer has classified occupational exposures to oxidized asphalt and its emissions during roofing as a "probable human carcinogen." During installation and removal of this product, including "hot mopped" application, workers must take precautions to assure adequate ventilation and use effective personal protective equipment to prevent exposures to dusts, fumes, vapors and mists. It is the responsibility of the contractor and workers to protect themselves and others in the work area from exposure to oxidized asphalt and its emissions when applying this product.

PRODUCT DATA¹

Reinforcement	2.0 lbs/100 sq ft - Fiberglass
Asphalt Modifier	SBS
Roll Weight	90 lbs (40.9kg)
Roll Size	48'2"x 39'-3/8" (14.7m x 1m)
Product Thickness	90 mils
Coverage	1.5 squares

¹All values stated as nominal



Construction Materials International, Inc
Address: 202 East 7th Avenue, Tampa, Florida 33602, USA
Tel: (+1)813-287-8265 / Fax: (+1) 813-287-8144
Email: sales@awg-llc.com / Web: www.cmi-us.com

TAMKO
BUILDING PRODUCTS